



M材質	Inner Hardness	Surface Hardness	Heat Treatment
	I.H内部硬度	S.H表面硬度	熱處理
SKH51	HRC58°~60°	HRC58°~60°	真空處理 Vacuumed

D	H	Catalog No.			L					
		Type	d	容許差 Tolerance	100	150	200	250	300	
3	4	JH003	0.8	-0.01 -0.02	23.6	28				
			0.9		22.2	28				
			1.0		22.2	26				
			1.1		21.2	24.6	32			
			1.2		19.2	22.2	30			
			1.3		19.2	22.2	30			
			1.4		19.2	22.2	30			
			1.5		19.2	22.2	30			
			1.6		19.2	22.2	28			
			1.7		19.2	22.2	28			
4	4		1.8		19.2	22.2	28			
			1.9		19.2	22.2	28			
			2.0		19.2	22.2	26	42.8		
5	4		2.1		22.2	26	28	55.2		
6	4		2.5		22.2	26	28	47.2		
7	6 (4)		3.0		22.2	27	30.4	43.8	56.4	
			3.5		28	30.6	34.2	51.4	67.6	
4.0		28	33	35.6	55.2	71.2				
9		4.5	33	34.2	36.8	63.8	82.4			
		5.0	33	34.2	36.8	63.8	83.6			
10		5.5	34.2	35.6	40.4	73.8	89.6			
		6.0	34.2	35.6	40.4	73.8	94.6			
11		8(4)	6.5		47.2	51.4	91.6	117.6		
		8(6)	7.0		47.2	51.4	99	129.2		
13		8(4)	8.0		64.4	71.6	120.6	136.4		
14	8	9.0		80.2	90.4	140.6	180.8			
15	8(4)	10.0		106	120.6	200	200			
16	8	11.0		121.8	142.2	211	211			
17	8(4)	12.0		154.8	163.8	239.6	239.6			

● Order: Catalog No. [D] x [H] x [d] x [L]

備注：圓面以外規格可定制

2D下載

3D下載

返回索引